## **SMARTEC**®

Work Function System









**Total electric system solution** 

**Advanced safety features** 

Torque limiting to protect system

**Integrated self diagnostics** 

Regenerative braking

No brushes for extended motor life

Voltage compensation limits speed droop

Zero maintenance

No belts or pulleys

**Environmentally friendly** 

Convenient

**Speed control** 

**Computer controlled system** 

**Current limiting protection** 



## **SPECIFICATIONS**

| Work Function System         |            |                                  |
|------------------------------|------------|----------------------------------|
| Controllers                  | quantity   | 1                                |
| Motors                       | quantity   | 2                                |
| Motor Package Size           |            |                                  |
| Height (Total)               | in [mm]    | 6.33 [160.78]                    |
| Height (Above mount surface) | in [mm]    | 3.98 [101.09]                    |
| Diameter                     | in [mm]    | 6.92 [175.77]                    |
| Motor Shaft Diameter         | in [mm]    | 1 [25.4]                         |
| Controller Package Size      |            |                                  |
| Height                       | in [mm]    | 3.745 [95.1]                     |
| Width                        | in [mm]    | 9.80 [248.9]                     |
| Length                       | in [mm]    | 8.41 [213.6]                     |
| System Voltage               |            |                                  |
| Nominal Battery Voltage      | VDC        | 48                               |
| Maximum                      | VDC        | 55                               |
| Minimum                      | VDC        | 42                               |
| Motor Speed                  | rpm        | 2800                             |
| Output Torque                |            |                                  |
| Peak                         | lb-ft [Nm] | 4.16 [5.64]                      |
| Continuous                   | lb-ft [Nm] | 3.1 [4.2]                        |
| Motor Mount                  |            | Four 5/16-24 tapped holes        |
| 90° Bolt Pattern Diameter    | in [mm]    | 6.15 [156.21]                    |
| Motor Shaft End              |            | Double "D" w/ 1/2-13 tapped hole |
| Start/Stop Time              | sec        | 2.5 - 3.5                        |
| Weight of Motor              | lb [kg]    | 13.7 [6.2]                       |
| Weight of Controller         | lb [kg]    | 9.5 [4.3]                        |

 $Specifications \ subject \ to \ change \ without \ notice.$ 







